

2

CAT 6A FTP RJ-45 Patch Panel



Benefits & Features

- Exceptional material properties and design
- Integrated full installation accessories (supplied free of charge), including labels and icons, clip organizers and T-raps- providing a simple and elegant cable termination and identification.
- Optional plastic front panels
- Optional back-side cable management with clip organizer and trap connection - providing simple and easy cable handling.
- Exceeding Category 6 performance - providing full support to Gigabit Ethernet over Category 5e and Category 6 cabling systems.
- High quality metal casing
- Compatible with 24-22 AWG solid conductors
- Available in T568A, T568B or Universal pin/pair assignment

Genel Özellikler	
	CAT 6A FTP RJ-45
Wire size range	22 to 26 AWG, Solid or stranded Cables
Material of construction	SPCC
Standard Color	Grey
Connector module holder	High impact, Flame-retardant plastic compound, UL 94 V-0
Housing material	High impact, Flame-retardant plastic compound, UL 94 V-0
Storage temperature range	-20 to +80C
Temperature operating range	-40 to +60C
Packaging	One unit per box
Keystone Jack Çakım Tipi	LSA
Çakılması Uygun Kablo İletken Kesitleri	22 - 26 AWG arası, katı veya esnek (7 telli) iletkenli kablolar
Çalışma Frekansı	500 MHz, 10 Gigabit
Paketleme	1 adet/kutu